

## PROTECT YOUR ASSETS, PROTECT YOUR LIFE!

## **OUR SERVICES**



PROTENC is an automatic autonomous fire extinguishing device that serves to protect enclosed spaces



#### **PROTENG PRESENTATION**

We will provide professional presentation of **all PROTENG products**.



**CONSULTING IN FIRE SAFETY** 



#### **PLANNING FIRE SAFETY**



#### **REGULAR SERVICE**

If necessary, we provide service of all PROTENG products.



#### **SALES SUPPORT**

We help our business partners to support sales in the area.

## **PRODUCTS**











#### **USE OF PROTENG PRODUCTS**



































































# TECHNICAL PARAMETERS



Product	PROTENG 100	PROTENG HD100	PROTENG 250	PROTENG HD250
Polyamide hose	Diameter 18mm	Diameter 18mm	Diameter 18mm	Diameter 18mm
Extinguishing volume	100g/cca 0,25m3	100g/cca 0,5m3	250g/cca 0,5m3	250g/cca 0,5m3
Hose length	450mm	600mm	1 100mm	1 250mm
Extinguishing agent	Heptafluoropropan (FM-200)	Heptafluoropropan (FM-200)	Heptafluoropropan (FM-200)	Heptafluoropropan (FM-200)
Starting the system	At a temperature above 90°C	At a temperature above 100°C	At a temperature above 100°C	At a temperature above 100°C

Product	PROTENG 500	PROTENG HD500	PROTENG 1000	PROTENG HD1000
Polyamide hose	Diameter 18mm	Diameter 18mm	Diameter 18mm	Diameter 18mm
Extinguishing volume	500 g/cca 1m3	500 g/cca 1m3	1 000 g/cca 2m3	1 000 g/cca 2m3
Hose length	2 100mm	2 450mm	4 100mm	4 900mm
Extinguishing agent	Heptafluoropropan (FM-200)	Heptafluoropropan (FM-200)	Heptafluoropropan (FM-200)	Heptafluoropropan (FM-200)
Starting the system	At a temperature above 90°C	At a temperature above 100°C	At a temperature above 90°C	At a temperature above 100°C

## EFFICIENCY AND CERTIFICATES



#### **EXTINGUISHING EFFECT**

- Cooling space
- Displacement of oxygen from space
- Stopping the free development of fire
- Extinguishing process is not toxic
- ✓ The system works fully automatically without operator
- ✓ No side effects



-ISO9001:2016

-ISO14001:2016 -ISO45001:2019 -AQAP2110:2016













-27MD S-01802

-Č.k. Z489/2020

-AS5062:2016Standard

-2017-Efectis-R000223

-BM OKF350000/11645-1/20217


-GARZ2.EX5036

# PROTENG PRODUCT TESTING



### **Location of thermocouples**


When testing the fire extinguishing system, you can see the location of individual **PROTENG 500 thermocouples** in the figure below




## PROTENG PRODUCT TESTING



## Visual display of the difference in case of fire








#### FIRE PROTECTED BY EXTINGUISHING SYSTEM

## PROTENG PRODUCT TESTING



#### The view of thermal camera



- Testing of product PROTENG 500
- When the system is activated, the fire temperature reaches a maximum of 200 °C
- This is followed by cooling of the space and extinguishing the fire



- After extinguishing, the maximum of the space temperature is 138°C
- No toxic waste is produced during firefighting
- The area can be checked immediately

## TSS PROTENG 01



**TSSPROTENG 01** is an additional information module for **PROTENG** fire extinguisher device, which informs the driver in the event of a fire via an LED and acoustically.



The device is powered by the battery in the vehicle.

Functionality check - each time the vehicle is started, modul informs the driver about the functionality.



In the event of a fire, the module informs the driver visually with a flashing LED



and acoustic signaling by a continuous beep.

The fire alarm can be deactivated manually until the next start of vehicle.

## TSS PROTENG 02



**TSSPROTENG 02** is an additional GPS monitoring system for the **PROTENG** fire extinguisher device. In the event of a fire, it notifies users via a mobile application and is equipped with its own battery.



The device does not need external power, it is powered only by the internal battery.

Low battery alert - the device automatically sends information.



The module sends the current position at regular 24-hour intervals, when it wakes up only for a moment, sends the position to the server and goes back to sleep mode, thus saving battery power.

Automatic function check - the server notifies the user in case of loss of connection with the module.



The device does not require professional installation.





## TSS PROTENG 03



TSSPROTENG 03 is an online monitoring system for PROTENG fire extinguisher device, which informs in the event of a fire via a mobile application or directly non-stop dispatching.











## TSSPROTENG CLASSIC

- Immediate information about fire
- Immediate information about signal lost
- Communication via mobile application

#### **TSS**PROTENG

#### CLASSICPRO

- Immediate information about fire
- Immediate information about signal lost
- Communication via mobile application
- System connected to non-stop dispatching

## TSSPROTENG PREMIUM

- Immediate information about fire
- Immediate information about signal lost
- Communication via mobile application and web interface
- System connected to TSSMONITORING


## TSSPROTENG PRFMIIIMPRO

- Immediate information about fire
- Immediate information about signal lost
- Communication via mobile application and web interface
- System connected to TSSMONITORING
- System connected to non-stop dispatching

It is possible to connect additional sensors (such as pressure, temperature, motion sensors, smoke detectors, and others) to the TSSPROTENG system.

# PROTENG REPRESENTATION IN THE WORLD





Australia, New Zealand, New Guinea

## OUR REFERENCES



- -Property Management VIRTUAL PORT PROPERTIES / ES
- -Transport company AZRIA PRESTIGE / ES
- -Transport company PRAHA, OSTRAVA / CZ
- -Transport company Budapest / HU
- -Transport company Volánbusz / HU
- -Transport company CREDO / HU
- -Waste Company OLO / SK
- -ALLIANCE NATO / EU
- -Transport company Slovak Lines / SK
- -Transport Company Arriva Nitra / SK
- -Railway Company Železničná Spoločnosť Slovensko / SK
- -Transport Company Blaguss / SK
- -National Highway Company Národná Diaľničná Spoločnosť / SK

- -Police Department Miami / USA
- -Experimental Aircraft Association (EAA) / USA
- -Aeromobil / SK
- -International Airport Baltimore, Meryland / USA
- -PROflo, Ohio / USA
- -International Airport Fort Lauderdale Executive, Florida / USA
- -National Indoor RV Center Dallas, Texas / USA
- -TIFFIN Motorhomes, Alabama / USA
- -Van Bordel Aircraft, Texas Cessna aircraft / USA
- -Ohio Columbus University / USA













































## CONTACT DETAILS





#### PROTENG SPAIN S.L.

CTRA N-340, KM 176, C.C. Oasis, Local 1, Marbella, Málaga, España

- @ info@protengspain.com
- www.protengspain.com
- **%** +34 951 627 099 | +34 613 20 51 04
- f @protengspain
- @protengspain
- @ @protengspain
- 🗶 @protengspain
- @protengspain

# THANK YOU FOR YOUR ATTENTION

